

## A global, spatially-explicit assessment of irrigated croplands influenced by urban wastewater flows

This content has been downloaded from IOPscience. Please scroll down to see the full text.

2017 Environ. Res. Lett. 12 074008

(<http://iopscience.iop.org/1748-9326/12/7/074008>)

View [the table of contents for this issue](#), or go to the [journal homepage](#) for more

Download details:

IP Address: 220.247.212.35

This content was downloaded on 06/07/2017 at 09:05

Please note that [terms and conditions apply](#).

You may also be interested in:

[Wastewater treatment and reuse in urban agriculture: exploring the food, energy, water, and health nexus in Hyderabad, India](#)

Leslie Miller-Robbie, Anu Ramaswami and Priyanie Amerasinghe

[Global assessment of urban and peri-urban agriculture: irrigated and rainfed croplands](#)

A L Thebo, P Drechsel and E F Lambin

[Integrated crop water management might sustainably halve the global food gap](#)

J Jägermeyr, D Gerten, S Schaphoff et al.

[Mapping water availability, projected use and cost in the western United States](#)

Vincent C Tidwell, Barbara D Moreland, Katie M Zemlick et al.

[Sustainability of global water use: past reconstruction and future projections](#)

Yoshihide Wada and Marc F P Bierkens

[Modelling the impact of sanitation, population growth and urbanization on human emissions of Cryptosporidium to surface waters—a case study for Bangladesh and India](#)

Lucie C Vermeulen, Jelske de Kraker, Nynke Hofstra et al.

[Urban agriculture: a global analysis of the space constraint to meet urban vegetable demand](#)

F Martellozzo, J-S Landry, D Plouffe et al.

[Hotspots of land use change in Europe](#)

Tobias Kuemmerle, Christian Levers, Karlheinz Erb et al.

[A global map of urban extent from nightlights](#)

Yuyu Zhou, Steven J Smith, Kaiguang Zhao et al.

# Environmental Research Letters



## LETTER

# A global, spatially-explicit assessment of irrigated croplands influenced by urban wastewater flows

### OPEN ACCESS

#### RECEIVED

31 December 2016

#### REVISED

19 April 2017

#### ACCEPTED FOR PUBLICATION

31 May 2017

#### PUBLISHED

5 July 2017

Original content from this work may be used under the terms of the [Creative Commons Attribution 3.0 licence](https://creativecommons.org/licenses/by/3.0/).

Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.



A L Thebo<sup>1,5</sup>, P Drechsel<sup>2</sup>, E F Lambin<sup>3,4</sup> and K L Nelson<sup>1</sup>

<sup>1</sup> Department of Civil and Environmental Engineering, University of California, Berkeley, O'Brien Hall, Berkeley, CA 94720, United States of America

<sup>2</sup> International Water Management Institute, 127 Sunil Mawatha, Pelawatte, Battaramulla, Sri Lanka

<sup>3</sup> School of Earth, Energy, and Environmental Sciences and Woods Institute for the Environment, Stanford University, 473 Via Ortega, Stanford, CA 94305, United States of America

<sup>4</sup> Georges Lemaitre Centre for Earth and Climate Research, Earth and Life Institute, Université catholique, de Louvain, Place Louis Pasteur 3, B-1348 Louvain-la-Neuve, Belgium

<sup>5</sup> Author to whom any correspondence should be addressed.

E-mail: [thebo@berkeley.edu](mailto:thebo@berkeley.edu)

**Keywords:** indirect water reuse, water quality, GIS, spatial analysis, return flow ratio, urban sanitation, wastewater treatment

Supplementary material for this article is available [online](#)

## Abstract

When urban areas expand without concomitant increases in wastewater treatment capacity, vast quantities of wastewater are released to surface waters with little or no treatment. Downstream of many urban areas are large areas of irrigated croplands reliant on these same surface water sources. Case studies document the widespread use of untreated wastewater in irrigated agriculture, but due to the practical and political challenges of conducting a true census of this practice, its global extent is not well known except where reuse has been planned. This study used GIS-based modeling methods to develop the first spatially-explicit estimate of the global extent of irrigated croplands influenced by urban wastewater flows, including indirect wastewater use. These croplands were further classified by their likelihood of using poor quality water based on the spatial proximity of croplands to urban areas, urban wastewater return flow ratios, and proportion of wastewater treated. This study found that 65% (35.9 Mha) of downstream irrigated croplands were located in catchments with high levels of dependence on urban wastewater flows. These same catchments were home to 1.37 billion urban residents. Of these croplands, 29.3 Mha were located in countries with low levels of wastewater treatment and home to 885 million urban residents. These figures provide insight into the key role that water reuse plays in meeting the water and food needs of people around the world, and the need to invest in wastewater treatment to protect public health.

## 1. Introduction

Despite significant investments in wastewater treatment infrastructure, levels of treatment in rapidly urbanizing, low-income urban areas are not keeping pace with population growth [1, 2]. Globally, less than 10% of collected wastewater receives any form of treatment [3, 4]. Concomitantly, agriculture is the largest water user in most countries, representing 70% of total global water withdrawals [5]. The reuse of untreated wastewater return flows in irrigated agriculture is commonplace downstream of urban areas [6]. As upstream regions have urbanized, surface

water sources have become effluent dominated, resulting in widespread indirect or *de facto* water reuse [7]. In other instances, farmers deliberately extract water from drains or sewage pipes [8]. In these cases, regional water scarcity and/or readily available access to wastewater are primary motivations. Wastewater provides a consistent, reliable source of water where other sources do not exist [9].

The use of wastewater (both treated and untreated) in irrigated agriculture has been documented in more than sixty countries, though the true scale of the practice is likely underestimated [10, 11]. Using government reported statistics and case studies,

Jiménez and Asano estimated that, globally, upwards of 4.5 Mha of croplands were irrigated with wastewater [12]. Their estimate does not capture the reuse of diluted, untreated wastewater downstream of urban areas [11]. A global projection by Scott *et al* estimated that 20 Mha of croplands were irrigated with raw, diluted, or partially treated wastewater. This widely cited number is an estimate based on expert opinion rather than on a spatially-explicit analysis [10]. Although numerous case studies indicate that irrigation with raw, diluted, or partially treated wastewater is widespread, the true extent of irrigation with untreated wastewater remains a knowledge gap.

Van der Hoek identified a key challenge in quantifying the extent of agricultural water reuse: the ambiguity of the term wastewater irrigation [10]. Most of what is documented is the direct reuse of wastewater, defined as the practice of using wastewater from sewers or wastewater treatment plants to irrigate crops without intermediate discharge to a receiving waterbody [12]. However, the majority of agricultural water reuse globally is the indirect or *de facto* reuse that occurs when wastewater is a dominant component of available surface water flows. Effluent from wastewater treatment plants can constitute a major portion of available surface water downstream of urban areas [13]. Consequently, alternate water reuse strategies such as industrial or domestic reuse or spatial redistribution of wastewater return flows, can have significant impacts on downstream farmers reliant on these urban wastewater return flows [14].

The use of wastewater in irrigated agriculture is often economically motivated. The reliability of wastewater flows can allow farmers to cultivate higher value, more water intensive vegetable crops than they could in the absence of the wastewater source [15–17]. Ensink *et al* documented that farmers in Pakistan were willing to pay more for wastewater than canal water because the nutrients in wastewater allowed them to reduce expenditures on fertilizers [18]. Similarly, farmers in Mexico protested the construction of a wastewater treatment plant, fearing that the facility would reduce concentrations of nutrients relative to the existing untreated wastewater [19]. Despite these benefits, the use of untreated wastewater can pose substantial health risks to those cultivating, selling, and consuming these agricultural products [20, 21].

Anecdotal evidence and case studies suggest that where treatment is lacking or insufficient, irrigation with untreated wastewater is a long-standing and widespread practice. However, its true extent, and therefore the magnitude of its risks, costs, and benefits remain largely unknown [6, 8]. Understanding the scale of wastewater reuse in irrigated agriculture is essential for garnering the attention of policy makers and sanitation practitioners such that infrastructure is selected in a manner sensitive to downstream water quality and quantity, public health, and the livelihoods of farmers reliant on wastewater for irrigation.

The objective of this study was to develop a globally consistent, spatially-explicit estimate of the global extent and distribution of the indirect reuse of wastewater in irrigated agriculture. In particular, we sought to identify irrigated croplands where wastewater constitutes a large proportion of available surface water and the subset of croplands likely to be irrigated with water with high levels of fecal contamination. A land use focused methodology was developed to understand the spatial relationships between upstream wastewater discharges (both treated and untreated) and downstream agricultural water users.

## 2. Methods

### 2.1. Classification overview and major data sources

A GIS-based algorithm was developed to classify irrigated croplands as a function of hydrologic connectivity between irrigated croplands and nearby urban extents, wastewater return flows, and regional levels of wastewater treatment. These methods were developed to quantify indirect reuse, but areas of direct reuse were also quantified when intersecting a stream channel. The two main outcomes were identifying: (1) the global extent of wastewater dependent irrigated croplands and (2) the subset of those croplands with a high likelihood of irrigation with untreated wastewater.

Wastewater dependent croplands were defined as irrigated croplands located within 40 km downstream of an urban area with a population exceeding 50 000 and in a catchment where wastewater constituted at least 20% of available blue water. This second variable (wastewater as a percent of available blue water) is analogous to urban wastewater return flows (i.e. the volume of water returned to surface water bodies following use, divided by available blue water in the catchment). This usage is distinct from other common return flow ratio metrics focused on agricultural drainage or similar [14]. Irrigated croplands with a high likelihood of untreated reuse were defined as the subset of wastewater-dependent croplands located in countries where less than 75% of wastewater received some form of treatment (figures 1 and S1 [stacks.iop.org/ERL/12/074008/mmedia](https://stacks.iop.org/ERL/12/074008/mmedia)). Data sources are described in table S1.

### 2.2. Classification methods

#### 2.2.1. Data pre-processing and identification of downstream irrigated croplands

The focus of this analysis (parts 1 and 2 in figure 1 and S1) was to reduce the MIRCA2000 irrigated croplands data [22] to only include peri-urban irrigated croplands located downstream of urban areas [23]. The maximum monthly irrigated croplands data from MIRCA2000 were limited to those within 40 km of an urban area with a population exceeding 50 000. These data were then overlaid with the stream channel network from the global drainage basin database [24] and all irrigated cropland gridcells not intersecting a




Figure 1. Overview of irrigated croplands classification logic.

stream channel were removed from consideration. On-stream irrigated cropland gridcells were then joined to urban areas and compared on the basis of their relative flow accumulation and position in the stream network (see online supplementary information). The product of this analysis will be referred to as downstream irrigated croplands (DSIC) for the remainder of this paper.

Two primary rationales were used in selecting a population threshold of 50 000. Review of the International Utility Benchmarking Network (IBNET) data [25] showed that sewerage and wastewater treatment were uncommon in low and middle income cities of less than 50 000 people. We previously found that a population threshold of 50 000 reached a reasonable balance between overestimating croplands

occurring around small towns and omitting larger towns with urban croplands [26]. A maximum distance threshold of 40 km from urban areas was selected based on the review of water quality data downstream of urban areas with low levels of wastewater treatment [27–30], with the intent to select a distance likely to be sufficient to reduce fecal contamination to the low levels required to reduce health risks to farmers and consumers of raw produce to acceptable levels [31, 32]. Additional analyses using thresholds of 10 and 20 km were also conducted to test the sensitivity of the results to this assumption.

### 2.2.2. Classification of DSIC by wastewater return flow ratio

The DSIC identified in the previous step were classified using catchment wastewater return flow ratio (RFR) to develop a measure of the relative dependence of DSIC on upstream wastewater flows (figure 1, part 3). The RFR of a catchment measures upstream urban wastewater discharges as a fraction of available blue water. RFR was used in this analysis as an indicator of the contribution of urban wastewater flows to downstream water availability. We used the catchment-scale RFR developed through the AQUEDUCT database, which was developed based on FAO's AQUASTAT database and global hydrologic modeling efforts [33, 34].

### 2.2.3. Classification of DSIC by percent of urban wastewater treated

DSIC in high RFR catchments were further classified to estimate their likelihood of using untreated or partially treated wastewater for irrigated agriculture (figure 1, part 4). The best data currently available on urban wastewater collection and treatment are the compilations by Baum *et al* [35], the Environmental Performance Index (EPI) [36], and Sato *et al* [37]. All three rely heavily on the FAO AQUASTAT database and/or Joint Monitoring Program Country reports [34]. IBNET data record information on sewerage and wastewater treatment reported by municipal utilities around the world, but only include a small subset of cities within participating countries [25]. After reviewing these datasets, we decided to integrate the three national level datasets to minimize data gaps (figure S2, methods in the online supplementary information). Given that this study is not modeling concentrations of pathogens or health risk, but the likelihood of untreated reuse, the broader availability of national level data motivated their use. The outcome of this step was the classification of DSIC by their relative likelihood of untreated wastewater reuse.

## 2.3. Additional data analysis

### 2.3.1. Downstream irrigated croplands by geographic region and distance downstream of urban areas

For each country, the sum of the DSIC area was divided by the total area of irrigated croplands to

estimate the fraction of irrigated croplands located downstream of large urban areas. The area of DSIC was also summed by catchment then divided by total catchment area to assess the fraction of the catchment land area allocated to DSIC. The methods described in sections 2.2–3 were repeated using 10 and 20 km buffers around urban areas to quantify the variation in the extent and distribution of DSIC 10, 20, and 40 km downstream of urban areas.

### 2.3.2. Urban population living in wastewater dependent catchments and catchments with a high likelihood of untreated agricultural water reuse

GRUMP urban area boundaries [23] with populations exceeding 50 000 people were intersected with GDBD catchment boundaries. The urban population densities associated with these urban areas [38] were then used to estimate the urban population within each catchment with DSIC. These values were then cross-tabulated against each of the different wastewater dependence and treatment classes.

### 2.3.3. Comparison of catchment area, DSIC, and population across wastewater treatment classes



The total catchment area (global non-polar land surface area), area of catchments containing DSIC, DSIC area, and population living in catchments with DSIC were summed for each wastewater dependence and treatment class for between class comparisons.

## 2.4. Validation

Estimates of overall accuracy and Kappa coefficients were used to validate the classification methods used to identify downstream irrigated croplands (2.2.1.) and irrigated croplands with a high likelihood of untreated wastewater reuse (2.2–3). An assessment of the available blue water and consumptive use data used to calculate return flow ratio in the AQUEDUCT database is included in Gassert *et al* [33]. See SI for additional details and confusion matrices.

To validate the DSIC classification algorithm, 400 irrigated cropland gridcells were randomly selected. Of these, 50% had been classified as DSIC and 50% had not. The validation gridcells were compared to the DEM, hydrography, and urban area GIS layers to evaluate whether the automated classification algorithm correctly differentiated downstream irrigated cropland pixels.

The UNGEMS water quality data on riverine fecal coliform concentrations [39] were used to validate the sub-classification of wastewater dependent irrigated croplands into those with a high or low likelihood of untreated reuse. Since the objective of this task was validation of the classification of the untreated reuse likelihood of DSIC, the UNGEMS data were pared down to only include monitoring stations that intersected DSIC and had multiple measures of fecal coliform from the year 2001 onwards ( $n = 63$  stations). These stations covered eleven countries and



more than 8858 fecal coliform measurements. DSIC classified as having a ‘high likelihood of untreated reuse’ and for which the mean observed fecal coliform concentrations exceeded 1000 CFU/100 ml were considered to be in agreement. Likewise, DSIC where observed fecal coliform concentrations were less than 1000 CFU/100 ml and classified as ‘not having a high likelihood of untreated reuse’ were also considered to be in agreement. A fecal coliform concentration of 1000 CFU/100 ml was selected based on its common usage as a threshold for irrigation water quality [20, 40, 41].

### 3. Results


#### 3.1. Extent of peri-urban croplands downstream of urban areas

55.1 Mha of irrigated croplands were located within 40 km downstream of or within an urban area. This area of DSIC constitutes approximately 26% of the global irrigated croplands identified by Portmann *et al* [42].

The mean percentage of DSIC across all countries was 23% (figure 2). Countries with high percentages of DSIC covered diverse hydrologic and socioeconomic conditions, including small island states/territories (mostly urban irrigated croplands), some European countries, and low to middle income countries with large urban areas (figure 2).

#### 3.2. Wastewater dependence of downstream irrigated croplands as a function of urban wastewater return flow ratio

65% of DSIC (35.9 Mha) were located in catchments where the RFR exceeded 20% (figures 3 and 4). 22.4 Mha (41%) of DSIC were located in catchments where wastewater return flows constituted the majority of available blue water (>50%), while 15.7 Mha (28%) were located in catchments where the RFR exceeded 80%—indicating that wastewater constituted an extremely high proportion of available surface water. Catchments with high values for these indicators were clustered around northern India, northern China, and Pakistan.



In many of these catchments, particularly those with monsoonal climates, surface runoff varies considerably between seasons, creating substantial seasonal variability in water availability. During low-flow periods, the RFR of catchments may be considerably higher than indicated here. 26.2 Mha (48%) of DSIC were located in a catchment with high seasonal variability in available water. Figure S3 shows catchments classified by both RFR and seasonal variability.

The distribution of DSIC across RFR classes was markedly different than the distribution of the land area of all catchments or catchments containing DSIC (figure S4). DSIC were disproportionately located in catchments with a RFR exceeding 20% (65% of DSIC) as compared to both the distribution of the land area of all catchments (14%) and the area of catchments with DSIC (30%). Urban populations residing in catchments with DSIC followed a similar distribution. 1.37 billion urban residents lived in catchments containing DSIC and a RFR exceeding 20% while 488 million people resided in catchments with extremely high wastewater dependence (RFR≥80%).


### 3.3. Distribution of wastewater dependent downstream irrigated croplands by level of urban wastewater treatment

In regions with low levels of wastewater treatment, DSIC were disproportionately located in catchments

with high, and in many cases, extremely high levels of wastewater dependence (figure 4). 45.1 Mha (82%) of DSIC were located in a country where less than 75% of wastewater received some form of treatment (figure 4). Of these croplands, 29.3 Mha (65%) were located in a wastewater dependent catchment (RFR ≥ 20%). This subset of wastewater dependent croplands (29.3 Mha) will be referred to as irrigated croplands with a high likelihood of untreated wastewater reuse. 885 million urban residents lived in catchments with a high likelihood of untreated wastewater reuse in irrigated agriculture. 14.7 million urban residents and 2.9 Mha of DSIC were present in catchments where the RFR exceeded 80% and less than 5% of wastewater was treated. Including total catchment populations, not just urban populations, would further increase the potentially affected populations.

### 3.4. Regional distribution of downstream irrigated croplands between wastewater dependent catchments and those with a high likelihood of untreated reuse

There was considerable variation in the spatial distribution of irrigated croplands with a high likelihood of untreated reuse across different countries and regions (figures 5 and S5–7; table S3). Five countries, China, India, Mexico, Pakistan, and Iran,



accounted for 25.1 Mha (85.7%) of DSIC with a high likelihood of untreated reuse (table S2). 42% of wastewater dependent irrigated croplands were located in countries where less than 25% of wastewater was treated. The mean level of wastewater treatment across all countries/territories was 23.8% with a median of 18.6%. The United States contained large areas of wastewater dependent DSIC (2.8 Mha), but, because most wastewater was treated, these DSIC were unlikely to have a high likelihood of untreated reuse.

### 3.5. Distribution of wastewater dependent downstream irrigated croplands by distance downstream

The analyses presented above (40 km limit) were repeated for downstream distances of 10 and 20 km (figure S8). 26.8 Mha of DSIC were within 10 km, 5.7 Mha were within 10 to 20 km, and 3.4 Mha were within 20 to 40 km of urban areas. Wastewater dependent DSIC within most regions followed a similar pattern. In Southeast Asia, North Africa, and Sub-Saharan Africa 92%, 98%, and 99% of DSIC, respectively, were located within 10 km of urban areas. South Asia was a notable exception, with the majority (56%) of DSIC located 10 to 40 km downstream of urban areas.

### 3.6. Validation of classification methods

When data were available to do so, classification methods were independently validated for classification accuracy and inter-rater agreement (Cohen's kappa) (tables 1, S4, and S5). Some initial assumptions were made following a critical review of the literature and/or available data. In those instances, the impact of different threshold values on study results was examined (figures 4 and S8). Further details on the validation methods, confusion matrices, and critical reviews are included in the online supplementary information (tables S4–S5).

## 4. Discussion

### 4.1. Interpretation of findings

Lack of a comprehensive, spatially-explicit global estimate of wastewater reuse in irrigated agriculture was a primary motivation for this study. Quantifying indirect reuse has proven particularly challenging for previous studies as it often occurs as an unplanned or *de facto* practice downstream of urban areas with wastewater discharges. In this assessment, our methods primarily captured indirect reuse and instances of direct reuse occurring in close proximity to stream channels.

We used a spatially based decision tree approach to integrate disparate datasets on irrigated croplands, hydrography, water use, wastewater collection and treatment. Starting with a base of all irrigated croplands (identified via MIRCA2000), we identified 35.9 Mha of DSIC in wastewater dependent catchments, of which 29.3 Mha were located in countries with low levels of wastewater treatment (figure 4). Reuse of untreated wastewater appears to be the most common form of agricultural water reuse, but it is generally poorly accounted for under traditional water accounting and management approaches.

A major challenge in both this analysis and global monitoring efforts more broadly is the lack of municipal level data on the level of wastewater treatment and proportion of flows treated. However, even when data are available, they often do not reflect the true operational status of wastewater treatment plants that may be present [43]. This paucity of data motivated our use of national level data on urban wastewater treatment. Even at the national scale, previous researchers have identified major data gaps in the quantification of the proportion and quantity of wastewater receiving some form of treatment [35–37]. While comprehensive higher resolution data would obviously provide more accurate local estimates, we

**Table 1.** Summary of assumptions, and methods used for review and validation.

Analysis or assumption	Validation method/metric	Validation data/review	Results	Interpretation
Identification of downstream irrigated croplands	Assessment of classification accuracy (overall accuracy +kappa)	Manual review of hydrography, urban land cover data, flow accumulation and flow direction rasters relative to irrigated cropland location	Overall accuracy: 0.96 Kappa: 0.92	DSIC classification algorithm is effectively classifying DSIC.
Irrigated croplands within 40 km downstream of an urban area have a higher likelihood of using surface water sources whose quantity and/or quality has been influenced by municipal wastewater discharges	Sensitivity analysis + critical review	DSIC and 'high likelihood of untreated reuse' DSIC within 10, 20, and 40 km of urban areas	Wastewater dependent DSIC within 10 km of urban area: 26.8 Mha (74.6%) High likelihood DSIC within 10 km of urban areas: 21.3 Mha (72.7%)	While a threshold of 40 km downstream was used, most wastewater dependent irrigated croplands were located within 10 km of urban areas
National level data on wastewater treatment as a proxy for high/low level of wastewater treatment	Critical review	Review of utility level data from IBNET relative to national data on wastewater data	Treatment of the full effluent volume and/or treatment to at least a secondary level was uncommon in low and middle income countries.	National statistics generally overestimate the true level of treatment from a water quality perspective.
Catchment return flow ratio <sup>a</sup> + percent of wastewater treated is an effective proxy for identification of rivers likely to be influenced by untreated municipal wastewater flows	Assessment of classification accuracy (overall accuracy + Kappa)	Comparison of untreated reuse classification algorithm results to WHO fecal coliform threshold for the use of wastewater in irrigated agriculture (1000 CFU/100 ml) (data from UNGEMS)	Overall accuracy: 0.86 Kappa: 0.69	Classification algorithm is effectively differentiating irrigated croplands with a high vs. low likelihood of dependence on untreated wastewater

<sup>a</sup> Assessment of input data used to estimate RFR (available blue water and consumptive use) was included in [33].

believe that the uncertainty introduced by using national level data resulted in conservative national and global estimates. Municipal-level estimates of wastewater treatment in the IBNET data tended to be lower than national estimates across all city size classes suggesting that our values present a conservative estimate of the fraction of untreated wastewater entering surface water irrigation sources. Where data on wastewater treatment were present in the IBNET data, secondary treatment was uncommon, further supporting the assumption that the national values are quite conservative and likely overestimate the true level of wastewater treatment.

The reuse of wastewater in agriculture can present health risks when upstream wastewater flows are inadequately treated. The use of poor quality water in irrigated agriculture has the potential to impact farmers, laborers, market vendors, and consumers across the produce supply chain. However, the level to which these risks are realized depends upon irrigation and cultivation practices, crop type, post-harvest handling, food safety and preparation practices (e.g. raw versus cooked) [20, 44, 45]. While our study does not address the crop types being grown in downstream irrigated croplands, past studies suggest that, particularly in low and middle income countries, vegetable

crops are grown more often in these regions than in rural areas [46].

Even when wastewater flows are treated, upstream wastewater return flows are generally not subject to traditional water rights apportionments, potentially leaving farmers vulnerable to municipal reallocation of wastewater flows for other types of water reuse (e.g. industrial, indirect potable, etc), alteration of flow timing, and overall reductions in flows resulting from water conservation efforts [14, 47, 48]. We found that 65% of DSIC were located in a catchment with high levels of dependence on urban wastewater flows. These same catchments were home to 1.37 billion urban residents of whom 885 million lived in areas where less than 75% of wastewater is treated. These figures highlight the role of indirect wastewater reuse in meeting the water and food needs of people around the world.

#### 4.2. Comparison to previous assessments of water reuse in irrigated agriculture

The top five country level estimates of wastewater dependent irrigated croplands likely to be practicing untreated reuse identified in this study were compared in table 2 to the national areas of wastewater reuse identified in Annex 2 of Jiménez and Asano [12],

**Table 2.** Comparison of areas of agricultural water reuse identified in this study as compared to the areas included in the inventory compiled by Jiménez and Asano [12]. Countries included are those with the five largest areas of likely untreated reuse.

Country	From this study		From Jiménez and Asano [12]				$\sum$ WW dependent irrigated croplands (this study) $\sum$ Area irrigated with WW (untreated + treated) (Jiménez and Asano)
	Urban WW treatment (%)	$\sum$ DSIC with a high likelihood of untreated reuse (RFR >20% and WWT $\leq$ 75%) (ha)	Irrigated with WW (ha)	Irrigated with treated WW (ha)	Type of wastewater irrigation described in Jiménez and Asano	Original sources	
China	71.2	$10.4 \times 10^6$	$1.3 \times 10^6$ <sup>a</sup>	0+	Unclear (discussion focused on direct, municipal reuse, but text indicates indirect reuse common)	WRIS	8.0
India	22.0	$8.9 \times 10^6$	73 000	ND	Direct, untreated (data from 1985 inventory of 200 sewage farms)	WRIS; AAST, 2004; EPA, 2004	122
Pakistan	1.2	$2.9 \times 10^6$	32 500	ND	Direct, treated (partially)	WRIS; EPA, 2004	88
Mexico	53.9	$1.5 \times 10^6$	190 000	70 000	Direct and some indirect, treated and untreated	Jimenez, 2006; WRIS	5.6
Iran	4.2	$1.4 \times 10^6$	+ <sup>b</sup>	+ <sup>b</sup>	Unclear	WRIS; AAST, 2004; EPA, 2004; Jimenez, 2006	ND

<sup>a</sup> Jiménez and Asano indicate 'Data are confusing'.

<sup>b</sup> Jiménez and Asano indicate 'No data are available, although the practice is reported'

which is the most comprehensive estimate of agricultural reuse area prior to our study. While the overall trends in both studies were similar, the areas of irrigated croplands (likely to be practicing untreated reuse) identified by our study were much larger than those enumerated by Jiménez and Asano. Both studies were in agreement that China was the nation with the largest area of wastewater irrigation (table 2). However, we found an irrigated area eight times greater than those captured through the surveys and government statistics used by Jiménez and Asano.

Two reasons the reuse of untreated wastewater has been so difficult to account for are that unplanned practices are difficult to quantify via census based methods and the obfuscation of accurate data about this practice for political or economic reasons [12]. These factors, plus our focus on indirect reuse, were the likely reasons we identified larger areas.

#### 4.3. Limitations

The spatial resolution of the irrigated croplands data (9.2 km) is a central consideration when interpreting results. The irrigated croplands captured in the source data (MIRCA2000) tend to be large, contiguous areas [49]. Small, disconnected urban and peri-urban plots would generally not be captured, though these plots can be using the poorest quality water (e.g. irrigating directly from sewers) [8, 50, 51] and can make substantial contributions to the production of food calories [52].

This study focused primarily on catchments where the wastewater RFR exceeded 20%. However, in

catchments with high seasonal variability in water availability, wastewater return flows may constitute a significantly larger or smaller proportion of available water at different times of year. When considering health risks associated with the use of untreated wastewater or poor quality water for irrigation, even a wastewater RFR of a few percent could be enough to cause concentrations of waterborne pathogens in surface water sources to exceed WHO thresholds for acceptable risk [40]. The RFR and urban area population thresholds adopted here were purposely conservative. These results likely represent lower limits of both the area of wastewater dependent irrigated croplands and irrigated croplands with a high likelihood of untreated reuse.

In-stream concentrations of waterborne pathogens will vary spatially and temporally with a wide range of variables, including levels of exposure to solar radiation, flow velocities, association with settleable materials, and influent pathogen concentrations [53]. Given the range of factors potentially confounding predictions of waterborne pathogens downstream of urban areas, we instead opted for a land-use centric approach, focused on irrigated croplands and classification of watershed characteristics indicative of dependence on urban wastewater flows and untreated wastewater. In this analysis, we utilized downstream distance thresholds of 10, 20, and 40 km. Previous research has shown a strong association between watershed land use composition and waterborne pathogen concentrations across diverse contexts [54–57]. Large strides have been made recently in

global water quality models, but their resolution is still coarse (0.5 degrees) [58–60] or their coverage not global [61]. They are thus limited in their applicability to the typologies of agricultural water reuse investigated here.

Given these limitations, our results are most appropriately interpreted at the national to regional scales to identify areas with a high likelihood of wastewater dependence or untreated reuse. More detailed studies accounting for wastewater treatment infrastructure, flows, and water allocation at the basin scale are needed to better understand the extent of health risks and vulnerability posed by indirect water reuse at finer spatial resolutions and for specific stakeholder groups. For studies focused on specific catchments or agricultural activities downstream of urban areas, watershed scale models and assessments are more appropriate tools for evaluating the risks experienced by farmers and consumers.

## 5. Conclusion

Our analysis provides the first spatially-explicit global estimates of the extent to which irrigated croplands are influenced by wastewater, both treated and untreated, finding 35.9 Mha of irrigated croplands located in wastewater dependent catchments (RFR  $\geq$  20%), of which 82% (29.3 Mha) are located in countries where less than 75% of wastewater is treated. 86% of these irrigated croplands were located in five countries: China, India, Pakistan, Mexico, and Iran.

Our work found that the scale of the practice of wastewater irrigation is at least 50% larger than previous, highly uncertain estimates (4.5 to 20 Mha) extrapolated from case studies and government statistics. This study is also the first to develop methods explicitly including indirect reuse in its estimates of agricultural water reuse. Urban wastewater return flows and other non-consumptive uses are often poorly accounted for in large-scale water resources models, but clearly make major contributions to farmers dependent on surface water for irrigation.

Considerable strides have been made in increasing access to improved sanitation in urban areas, but for achieving the Sustainable Development Goal (SDG) 6, further significant investments in wastewater treatment are needed. Even when untreated wastewater constitutes a small percentage of flow, concentrations of pathogens in irrigation source water can far exceed those recommended in WHO guidelines. This study sheds further light on the often complicated ways in which urban areas impact agricultural water quality in downstream peri-urban and rural environments. Further work is needed to ensure that urban sanitation policies not only address the protection of surface water quality for ecological reasons, but also recognize the water quantity and quality needs of downstream farmers.

## Acknowledgments

Research support was provided through grants from the USAID Collaborative Research-CGIAR Linkage Fund (Award no. 4500012834), Stanford UPS Endowment (Grant no. 1139780), CGIAR Research Program on Water, Land and Ecosystems (WLE), and STAR Fellowship Assistance Agreement no. 91750501-0 awarded by the US Environmental Protection Agency (EPA). The authors thank J. Mateo-Sagasta (IWMI) for his constructive comments on an earlier version of this manuscript. It has not been formally reviewed by EPA. The views expressed in this publication are solely those of the authors, and EPA does not endorse any products or commercial services mentioned in this publication.

## References

- [1] Keraita B, Jimenez B and Drechsel P 2008 Extent and implications of agricultural reuse of untreated, partly treated and diluted wastewater in developing countries *CAB Rev. Perspect. Agric., Vet. Sci., Nutr. Nat. Res.* **3** 1–15
- [2] UNESCO & UN-Water 2017 *Wastewater: the untapped resource UN World Water Development Report 2017* (Paris: UNESCO)
- [3] Carpenter S, Pingali P, Bennett E and Zurek M 2005 *Millennium Ecosystem Assessment: Ecosystems and Human Well-being: Scenarios vol 2* (Washington, DC: Island Press)
- [4] United States Environmental Protection Agency 2012 *2012 Guidelines for Water Reuse*
- [5] Frenken K and Gillet V 2012 *Irrigation Water Requirement Water Withdrawal by Country* (Rome: Food and Agriculture Organization)
- [6] Raschid-Sally L and Jayakody P 2008 Drivers and characteristics of wastewater agriculture in developing countries: results from a global assessment *IWMI Research Report 127* (Colombo, Sri Lanka)
- [7] Buechler S and Devi G 2003 *Household Food Security and Wastewater-Dependent Livelihood Activities Along the Musi River in Andhra Pradesh, India* (Colombo, Sri Lanka: International Water Management Institute) ([http://publications.iwmi.org/pdf/H\\_34272.pdf](http://publications.iwmi.org/pdf/H_34272.pdf))
- [8] Ensink J H J, Mahmood T, Van Der Hoek W, Raschid-Sally L and Amerasinghe F P 2004 A nationwide assessment of wastewater use in Pakistan: an obscure activity or a vitally important one? *Water Policy* **6** 197–206
- [9] Santos L, Oweis T and Zairi A 2002 Irrigation management under water scarcity *Agr. Water Manage.* **57** 175–206
- [10] Scott C A, Faruqui N I and Raschid-Sally L 2004 *Wastewater Use in Irrigated Agriculture Confronting the Livelihood Environmental Realities* ed C A Scott, N I Faruqui and L Raschid-Sally (Cambridge, MA: CAB International)
- [11] Drechsel P, Scott C A, Raschid-Sally L, Redwood M and Bahri A 2010 *Wastewater Irrigation and Health: Assessing and Mitigating Risk in Low-income Countries* (London: Earthscan)
- [12] Jiménez B and Asano T 2008 *Water Reuse: An International Survey of Current Practice, Issues and Needs* (London: IWA Publishing)
- [13] Rice J and Westerhoff P 2014 Spatial and temporal variation in de facto wastewater reuse in drinking water systems across the USA *Environ. Sci. Technol.* **49** 982–9
- [14] Simons G W H, Bastiaanssen W G M and Immerzeel W W 2015 Water reuse in river basins with multiple users: a literature review *J. Hydrol.* **522** 558–71

- [15] Bradford A, Brook R and Hunshal C S 2003 Wastewater irrigation in Hubli-Dharwad, India: implications for health and livelihoods *Environ. Urban.* **15** 157–70
- [16] Keraita B B, Drechsel P and Amoah P 2003 Influence of urban wastewater on stream water quality and agriculture in and around Kumasi, Ghana *Environ. Urban.* **15** 171–8
- [17] Navarro I, Chavez A, Barrios J A, Maya C, Becerril E, Lucario S and Jimenez B 2015 Wastewater reuse for irrigation—practices, safe reuse and perspectives *Irrigation and Drainage—Sustainable Strategies and Systems* ed M S Javaid (Rijeka: InTech) (<https://doi.org/10.5772/59361>)
- [18] Ensink J H J, Van Der Hoek W, Matsuno Y, Munir S, Aslam M R and Van Der Hoek W 2002 Use of untreated wastewater in peri-urban agriculture in Pakistan: risks and opportunities *Research Report 64* (Colombo, Sri Lanka: International Water Management Institute) ([http://www.iwmi.cgiar.org/Publications/IWMI\\_Research\\_Reports/PDF/pub064/Report64.pdf](http://www.iwmi.cgiar.org/Publications/IWMI_Research_Reports/PDF/pub064/Report64.pdf))
- [19] Malkin E 2010 Fears that a lush land may lose a foul fertilizer *New York Times* A11 (5 May 2010) ([www.nytimes.com/2010/05/05/world/americas/05mexico.html](http://www.nytimes.com/2010/05/05/world/americas/05mexico.html))
- [20] Antwi-Agyei P, Cairncross S, Peasey A, Price V, Bruce J, Baker K, Moe C, Ampofo J, Armah G and Ensink J 2015 A farm to fork risk assessment for the use of wastewater in agriculture in Accra, Ghana *PLoS ONE* **10** e0142346
- [21] Silverman A I, Akromg M O, Amoah P, Drechsel P and Nelson K L 2013 Quantification of human norovirus GII, human adenovirus, and fecal indicator organisms in wastewater used for irrigation in Accra, Ghana *J. Water Health* **11** 473–88
- [22] Portmann F T, Siebert S and Döll P 2010 MIRCA2000—global monthly irrigated and rainfed crop areas around the year 2000: a new high-resolution data set for agricultural and hydrological modeling *Glob. Biogeochem. Cycles* **24** GB1011
- [23] Center for International Earth Science Information Network (CIESIN)—Columbia University, International Food Policy Research Institute (IFPRI), The World Bank and Centro Internacional de Agricultura Tropical (CIAT) 2011 *Global Rural-Urban Mapping Project, Version 1 (GRUMPv1): Urban Extents Grid*
- [24] Masutomi Y, Inui Y, Takahashi K and Matsuoka Y 2009 Development of highly accurate global polygonal drainage basin data *Hydrol. Processes* **23** 572–84
- [25] World Bank and Water and Sanitation Program 2014 IBNET (International Benchmarking Network for Water and Sanitation Utilities)
- [26] Thebo A L, Drechsel P and Lambin E F 2014 Global assessment of urban and peri-urban agriculture: irrigated and rainfed croplands *Environ. Res. Lett.* **9** 114002
- [27] Abraham W-R 2011 Megacities as sources for pathogenic bacteria in rivers and their fate downstream *Int. J. Food Microbiol.* **2011** 1–13
- [28] Weobong C A A, Jones K and Obiri-Danso K 2005 Aspects of health-related microbiology of the Subin, an urban river in Kumasi, Ghana *J. Water Health* **3** 69–76
- [29] Mladenov N, Strzepek K and Serumola O M 2005 Water quality assessment and modeling of an effluent-dominated stream, the Notwane River, Botswana *Environ. Monit. Assess.* **109** 97–121
- [30] Ensink J H J, Scott C A, Brooker S and Cairncross S 2010 Sewage disposal in the Musi-River, India: water quality remediation through irrigation infrastructure *Irrig. Drain. Syst.* **24** 65–77
- [31] Mok H F, Barker S F and Hamilton A J 2014 A probabilistic quantitative microbial risk assessment model of Norovirus disease burden from wastewater irrigation of vegetables in Shepparton, Australia *Water Res.* **54** 347–62
- [32] Ensink J H J, Blumenthal U J and Brooker S 2008 Wastewater quality and the risk of intestinal nematode infection in sewage farming families in Hyderabad, India *Am. J. Trop. Med. Hyg.* **79** 561–7
- [33] Gassert F, Landis M, Luck M, Reig P and Shiao T 2012 AQUEDUCT metadata document *AQUEDUCT Global Maps 2.0* (Washington, DC: World Resources Institute)
- [34] Food and Agriculture Organization 2015 *AQUASTAT Database*
- [35] Baum R, Luh J and Bartram J 2013 Sanitation: a global estimate of sewerage connections without treatment and the resulting impact on MDG progress *Environ. Sci. Technol.* **47** 1994–2000
- [36] Malik O A, Hsu A, Johnson L A and de Sherbinin A 2015 A global indicator of wastewater treatment to inform the sustainable development goals (SDGs) *Environ. Sci. Policy* **48** 172–85
- [37] Sato T, Qadir M, Yamamoto S, Endo T and Zahoor A 2013 Global, regional, and country level need for data on wastewater generation, treatment, and use *Agr. Water Manage.* **130** 1–13
- [38] Center for International Earth Science Information Network (CIESIN)—Columbia University and Centro Internacional de Agricultura Tropical (CIAT) 2005 *Gridded Population of the World, Version 3 (GPWv3): National Administrative Boundaries*
- [39] UN GEMS/Water Programme Office 2008 *Water Quality Outlook* (Burlington, ON: United Nations Environment Programme)
- [40] World Health Organization 2006 Guidelines for the safe use of wastewater, excreta, and graywater *Wastewater Use in Agriculture* vol 2 (Geneva: World Health Organization)
- [41] Akin E, Al-Salem S, Cairncross A, Schwartzbrod J, Shuval H I, Singh C N and Yanez F 1989 *Health Guidelines for the Use of Wastewater in Agriculture and Aquaculture* (Geneva: World Health Organization)
- [42] Portmann F T, Siebert S and Döll P 2010 MIRCA2000—Global monthly irrigated and rainfed crop areas around the year 2000: a new high-resolution data set for agricultural and hydrological modeling *Glob. Biogeochem. Cycles* **24** GB1011
- [43] Murray A and Drechsel P 2011 Why do some wastewater treatment facilities work when the majority fail? case study from the sanitation sector in Ghana *Waterlines* **30** 135–49
- [44] Mara D D, Sleigh P A, Blumenthal U J and Carr R M 2007 Health risks in wastewater irrigation: comparing estimates from quantitative microbial risk analyses and epidemiological studies *J. Water Health* **5** 39–50
- [45] Amoah P, Drechsel P, Abaidoo R C and Klutse A 2007 Effectiveness of common and improved sanitary washing methods in selected cities of West Africa for the reduction of coliform bacteria and helminth eggs on vegetables *Trop. Med. Int. Health* **12** 40–50
- [46] Simon D 2008 Urban environments: issues on the peri-urban fringe *Annu. Rev. Environ. Resour.* **33** 167–85
- [47] Macdonald D H, Lamontagne S and Connor J 2005 The economics of water: taking full account of first use, reuse and the return to the environment *Irrig. Drain.* **54** 93–102
- [48] Molle F and Berkoff J 2009 Cities vs. agriculture: a review of intersectoral water re-allocation *Nat. Resour. Forum* **33** 6–18
- [49] Siebert S, Döll P, Hoogeveen J, Faures J-M, Frenken K and Feick S 2005 Development and validation of the global map of irrigation areas *Hydrol. Earth Syst. Sci. Discuss.* **2** 1299–327
- [50] Qadir M, Wichelns D, Raschid-Sally L, McCornick P G G, Drechsel P, Bahri A and Minhas P S S 2010 The challenges of wastewater irrigation in developing countries *Agr. Water Manage.* **97** 561–8
- [51] Van Rooijen D J, Biggs T W, Smout I and Drechsel P 2010 Urban growth, wastewater production and use in irrigated agriculture: a comparative study of Accra, Addis Ababa, and Hyderabad *Irrig. Drain.* **24** 53–64
- [52] Samberg L H, Gerber J S, Ramankutty N, Herrero M and West P C 2016 Subnational distribution of average farm size and smallholder contributions to global food production *Environ. Res. Lett.* **11** 124010

- [53] Pachepsky Y, Shelton D R, McLain J E T, Patel J and Mandrell R E 2011 Irrigation waters as a source of pathogenic microorganisms in produce: a review *Advances in Agronomy* ed D L Sparks vol 113 (San Diego, CA: Elsevier Inc.) pp 75–141
- [54] Viau E J, Goodwin K D, Yamahara K M, Layton B A, Sassoubre L M, Burns S L, Tong H I, Wong S H C, Lu Y and Boehm A B 2011 Bacterial pathogens in Hawaiian coastal streams—associations with fecal indicators, land cover, and water quality *Water Res.* **45** 3279–90
- [55] Bradshaw J K, Snyder B J, Oladeinde A, Spidle D, Berrang E, Meinersmann R J, Oakley B, Sidle R C and Sullivan K 2016 Characterizing relationships among fecal indicator bacteria, microbial source tracking markers, and associated waterborne pathogen occurrence in stream water and sediments in a mixed land use watershed *Water Res.* **101** 498–509
- [56] Liang Z, He Z, Zhou X, Powell C A, Yang Y, He L M and Stoffella P J 2013 Impact of mixed land-use practices on the microbial water quality in a subtropical coastal watershed *Sci. Total Environ.* **449** 426–33
- [57] Walters S P, Thebo A L and Boehm A B 2011 Impact of urbanization and agriculture on the occurrence of bacterial pathogens and *stx* genes in coastal waterbodies of central California *Water Res.* **45** 1752–62
- [58] Vermeulen L C, Hofstra N, Kroeze C and Medema G 2015 Advancing waterborne pathogen modelling: Lessons from global nutrient export models *Curr. Opin. Environ. Sustain.* **14** 109–20
- [59] Vermeulen L C, De Kraker J, Hofstra N, Kroeze C and Medema G J 2015 Modelling the impact of sanitation, population and urbanization estimates on human emissions of *Cryptosporidium* to surface waters—a case study for Bangladesh and India *Environ. Res. Lett.* **10** 94017
- [60] Seitzinger S P *et al* 2010 Global river nutrient export: a scenario analysis of past and future trends *Glob. Biogeochem. Cycles* **24** GB0A08
- [61] Reder K, Florke M and Alcamo J 2015 Modeling historical fecal coliform loadings to large European rivers and resulting in-stream concentrations *Environ. Model. Softw.* **63** 251–63